
Sundance® Spas 880 Marin®

Specifications




Dimensions: ..... 76" x 91" x 34" (193.04 cm x 231 cm x 86.36 cm)
Seating Capacity: ..... 4-5 Adults
Dry Weight: ..... 803 lbs (364.23 kg)
Filled Weight (Spa Volume): ..... 4,222 lbs (1,915 kg)
Filled Weight (Average Fill): ..... 3,472 lbs (1,575 kg)
Water Capacity (Spa Volume): ..... 410 US Gal (1,552 Liters)
Water Capacity (Average Fill): ..... 320 US Gal (1,211 Liters)
Controls: ..... 880 iTouch Interface LCD Control, Displays Temperature, Time, Cycles and Jet/Air System Control. Offers Customizing of Filtration Cycles, Lighting, Water Temperature Setting and other features
Water Delivery: ..... 2 TheraMax High-Flow Pumps and 8-Hour Dynamic Flow Circulation System
Pump 1: ..... North America (60 Hz): 1-Speed/2.5 HP Continuous, 11.3A Max., 56 Frame
Export (50 Hz): 1-Speed/2.0 HP Continuous, 7.0A Max.
Pump 2: ..... North America (60 Hz): 1-Speed/2.5 HP Continuous, 11.3A Max., 56 Frame
Export (50 Hz): 1-Speed/2.0 HP Continuous, 7.0A Max.
Pump 3: ..... High Output Dynamic Flow, 8-Hour Filter/Circulation Pump (35 gpm) Programmable for Daily Start Time and Duration
Total Hydrojets: **45**
Seat A Jets: ..... 6 Fluidix Reflex, 2 Vortex, 2 Pulsator, 6 Focus-Relief®
Seat B Jets: ..... 2 Vortex, 4 Focus-Relief
Seat C Jets: ..... 2 Fluidix Nex, 12 Fluidix ST, 2 Accu-Pressure
Seat D Jets: ..... 2 Fluidix Nex, 1 Vortex, 2 Fluidix Intelli-Jet
Footwell Jets (E): ..... 2 Vortex
Air Blower: ..... High-Efficiency, 1-Speed
Aromatherapy Delivery: ..... 4 Air Injector Jets with Quiet High Speed Air Pump
Air Controls/Massage Selectors: ..... 4/1 (Standard air control with LED lights and massage selector with LED lights)
Filter: ..... MicroClean® Ultra Filtration System, 130 ft² (2 interlocking cartridge filters)
Water Treatment: ..... Automatic Brominator and Dynamic Flow Circulation System; Factory installed CLEAR**RAY**® Water Purification System and CLEAR**RAY**® PRO$_3$TECT™
Lighting: ..... Multi-Colored LED Lighting System (1 Waterfall, 1 Main Light, 4 Air controls, 1 Massage Selector, Exterior lights)
Skirt Cabinet (SunSide™): ..... Modern Hardwood, Brushed Gray and Vintage Oak (Equipped with Standard Exterior Lights)
Shell Colors: ..... North America: Platinum, Celestite (Gypsum), Sahara, Monaco, Midnight, Porcelain
Export (50 Hz): All North America Colors
Handrails: ..... None
Headrests: ..... Four, 1-Piece Gray
Heater: ..... North America (60 Hz): Low Flow 5.5 kW with Titanium Element
Export (50 Hz): Low Flow 2.7 kW with Titanium Element
Electrical Requirements: ..... North America (60 Hz): 240 VAC@40A, 50A or 60A;
Export (50 Hz): 230-240 VAC@1x40A or 1x16A/1x32A, 1x20A/1x16A, 3x16A (see manual for more configurations); or Suitably Rated Circuit Breaker to Comply with Local Electrical Regulations. Certain Countries May Require 2 Power Inputs; Two GFCI/RCD Breakers are Required for This Configuration.
Limited Warranty*: ..... North America (60 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 5 Years Jets, 2 Years Lights, 1 Year Stereo
Export (50 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 5 Years Jets, 2 Years Lights, 2 Years Stereo
Waterfall Feature: ..... Adjustable Flow Rate; Colored Lighting
Audio System (Optional): ..... Factory Installed BLUEWAVE® 2.0 Wireless Spa Stereo System with Auxiliary 3.5 mm headphone jack connection, Bluetooth® compatible, 4 premium speakers and a powered subwoofer
Special Features: ..... MicroClean® Plus Versatile Filter Lid, ***Optional*** Filter Lid Pillow seat, ***Optional*** (Factory Installed) SmartTub™ Module

*(See Warranty Document for Specific Details)

Dimensions/Specifications Subject To Change Without Notice

Sundance Spas 880 Marin

Operation/Seat Depths



Filter Lid is shown with aftermarket seat pillow

45 Total Jets



(A) Air Control - Activates Seat A Jets (6 Fluidix Reflex, 2 Pulsator, 2 Vortex)

(B) Massage Selector [Pump 2] - Adjusts Massage Level Between Seat A Jets and Seat C Jets

(C) Air Control - Activates Seat C Upper 8 Jets (2 Fluidix Nex, 6 Fluidix ST)

(D) Air Control - Activates Seat C Lower 8 Jets (6 Fluidix-ST, 2- Accu-Pressure)

(E) Waterfall Selector [8-Hour Circ. Pump] - Controls Waterfall Output

(F) Air Control - Activates Seat B Jets (2 Vortex) + Seat D Jets (2 Fluidix Nex, 1 Vortex, 2 Fluidix Intelli-Jet) + Footwell Jets (2 Vortex)

(G) Sunscent Dispenser

- Jets Pump 1: Seat B Jets + Seat D Jets + Footwell Jets are always on when this pump is running
- Focus-Relief Jets: Work with both the blower and Jets Pump 2. The blower introduces air to the jet and the Jets Pump forces water through.


Spa Operation Subject To Change Without Notice

SEAT DEPTHS

A = 25.75" (65.40 cm)
B = 24.50" (62.23 cm)
C = 27.75" (70.48 cm)
D = 22.00" (55.88 cm)
E = 25.50" (64.77 cm)
F = 29.50" (74.93 cm)

G = 31.25" (79.37 cm)

Listed dimensions represent distance from top of acrylic to lowest point in seat. **Tolerance ± 0.5" (1.27 cm).**




Dimensions/Specifications Subject To Change Without Notice

Sundance Spas 880 Marin


Portable Dimensions

TOP VIEW




FRONT/BACK VIEW

Tolerance: ± 0.5" (1.27 cm)



LEFT/RIGHT SIDE VIEW
(Left Side View Shown)


Tolerance: ± 0.5" (1.27 cm)



STOP

IMPORTANT! Always measure each hot tub for exact dimensions BEFORE designing its foundational support and/or decking.

STOP





Dimensions/specifications subject to change without notice. Tolerance: ± 0.5" (1.27 cm)

SunSide Dimensions

Spa Models	DIMENSIONS A-F (All measurements are an approximate)					
	A	B	C* *±0.25” (0.635 cm)	D	E	F
Maxxus	41.5" (105.41 cm)	18.5" (46.99 cm)	5.5" (13.97 cm)	12.0" (30.48 cm)	32.5" (82.55 cm)	73.5" (186.69 cm)
Aspen						
Optima	37.5" (95.25 cm)		3.75" (9.53 cm)	8.0" (20.32 cm)	32.25" (81.92 cm)	71.5" (181.61 cm)
Cameo						
Altamar						63.25" (160.65 cm)
Cambria	34" (86.36 cm)			7.5" (19.05 cm)	28.75" (73.03 cm)	58.25" (147.95 cm)
Marin						
Capri	30.5" (77.47 cm)	18" (45.72 cm)	3.5" (8.89 cm)	9.5" (24.13 cm)	25.5" (64.77 cm)	64.25" (163.19 cm)
DIMENSIONS G-I (All measurements are an approximate)						
	G	H	I			
Maxxus	8.0" (20.32 cm)	13.0" (33.02 cm)	3.5" (8.89 cm)			
Aspen						
Optima	7.0" (17.78 cm)	13.5” (34.29 cm)	1.5" (3.81 cm)			
Cameo						
Altamar	6.5" (16.51 cm)					
Cambria		13.0" (33.02 cm)				
Marin						
Capri	4.0" (10.16 cm)	14.5" (36.86 cm)				
- Dimensions Subject to Change Without Notice - Tolerance: ± 0.5” (1.27 cm)						

IMPORTANT! Always measure each hot tub for exact dimensions BEFORE designing its foundation support and/or decking.





An 18" clearance, all around the spa, is recommended. This clearance is needed for panel removal or when servicing.

NOTE: Over time the panel(s) may bow, this is considered normal. The panels will straighten out when reinstalled into the mounting channel. Place one end of the panel into the channel first then flatten the panel and insert the other end.

Tolerance: ± 0.5" (1.27 cm)

Denne modellen kan kobles med 1-fas 230V C-sikring (treg) og 3-fas (400 volt TN-nett - se egne linjer)

880-serien:

Marin:	For å få mest mulig glede av badet anbefaler vi høyeste kurs for optimal drift.			
	Type varmeelement	**Alternativ tilkobling**	**Funksjon**	**Kretskortinnstillinger**
Marin	5,5 kW	3-fas (400 volt TN-nett) 25 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Marin	5,5 kW	40 amp eller 20 + 25 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Marin	5,5 kW	25 amp	Alle pumper kan brukes samtidig. Varmeelementet slår seg automatisk av når pumpene startes.	Se brukermanual.
Marin	2,7 kW	3-fas (400 volt TN-nett) 16 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Marin	2,7 kW	32 amp eller 16 + 20 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Marin	2,7 kW	20 amp	Alle pumper kan brukes samtidig. Varmeelementet slår seg automatisk av når en av pumpene startes.	Se brukermanual.